



Deluxe Flush Range

LUXURY MARINE TOILETS

Now you can experience all the comforts of home at sea with the Jabsco range of Deluxe Flush marine toilets.

Jabsco is proud to announce the launch of our complete range of Deluxe Flush luxury marine toilets, with the addition of the new 14" toilet. Designed for the discerning owner looking for luxury and comfort, the Deluxe Flush Range features space saving stylish design with minimal water usage and virtually silent operation.

The Jabsco Deluxe Flush Range of 14" and 17" toilets all come complete with the new multi-function "one touch" control pad, which also adapts to standard Gewiss and Vimar fascia plates. They are all available with straight or angled backs for easy installation with a minimal footprint and come with a standard household size seat.

Features and Benefits

- Space saving stylish design
- Regular household size seat
- Virtually silent operation
- Fresh or raw water rinse models
- Non-clogging large bore flush pump macerates waste



a xylem brand

Deluxe Flush Range LUXURY MARINE TOILETS

The Deluxe Flush toilet range features a multi-function 'one touch' control pad offering four options - 'Fill', 'Quick Flush', 'Flush' or 'Empty'. In addition, the owner can set the control at any time so that the bowl is always left either 'Dry' or 'Wet' after flushing. The recommended 'Dry' setting minimizes total water usage. If water usage is not a concern, the 'Wet' setting automatically "Fills" the bowl after flushing, ready for the next user. Simultaneously holding down both 'Quick Flush' and 'Flush' buttons for 5 seconds switches between bowl always left 'Dry' and bowl always left 'Wet' modes.

- 'Fill' may be touched when the bowl is 'Dry' to add 1 quart (1 liter) of water before use, if thought necessary.
- 'Quick Flush' first rinses and then empties the bowl after light use. On 'Dry' setting, this uses less than 1 quart (1 liter) of water.
- 'Flush' rinses and empties the bowl twice after heavy use. If the bowl is 'Dry', touching 'Fill' before use is recommended. This uses just 2.5 quarts (2.5 liters) of water.
- 'Empty' does exactly what it says without adding any water, whenever desired. Even when the bowl is apparently 'dry', there is an anti-odor water lock in the pump housing.

"One-Touch" Control Pad



The Jabsco controller is supplied a standard surface mount unit with a clean white bezel. However, the controller design allows for the replacement of the standard bezel with any of the Geviss or Vimar facia plates. This gives the installer total flexibility with regards to surface mount or flush mount, with any of the colors or styles available in the Geviss or Vimar range.





Rinse Options

(1) 58020, 58040, 58060, 58080 Series are supplied with a combined solenoid valve and siphon breaker assembly for connection to any existing pressurized water system capable of delivering 2.9 GPM (11 LPM) or more. The siphon breaker ensures there is no backflow from the toilet into the water system.

(2) 58220, 58240, 58260, 58280 Series are supplied with a remote mounted self-priming pump to bring in sea, river or lake rinse water. Complete with Pumpgard™ strainer.

NEW! 14" MODELS	Description	Part No.	Rinse Water Variant	DC Voltage	Fuse/Breaker	
	Angled Back Variant	12V + Solenoid	58060-1012	Fresh	12V DC	25 amp
		24V + Solenoid	58060-1024	Fresh	24V DC	15 amp
	Straight Back Variant	12V + Rinse Pump	58260-1012	Raw	12V DC	25 amp
		24V + Rinse Pump	58260-1024	Raw	24V DC	15 amp
	Straight Back Variant	12V + Solenoid	58080-1012	Fresh	12V DC	25 amp
		24V + Solenoid	58080-1024	Fresh	24V DC	15 amp
	Angled Back Variant	12V + Rinse Pump	58280-1012	Raw	12V DC	25 amp
		24V + Rinse Pump	58280-1024	Raw	24V DC	15 amp

17" MODELS	Description	Part No.	Rinse Water Variant	DC Voltage	Fuse/Breaker	
	Angled Back Variant	12V + Solenoid	58020-1012	Fresh	12V DC	25 amp
		24V + Solenoid	58020-1024	Fresh	24V DC	15 amp
	Straight Back Variant	12V + Rinse Pump	58220-1012	Raw	12V DC	25 amp
		24V + Rinse Pump	58220-1024	Raw	24V DC	15 amp
	Straight Back Variant	12V + Solenoid	58040-1012	Fresh	12V DC	25 amp
		24V + Solenoid	58040-1024	Fresh	24V DC	15 amp
	Angled Back Variant	12V + Rinse Pump	58240-1012	Raw	12V DC	25 amp
		24V + Rinse Pump	58240-1024	Raw	24V DC	15 amp



Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.

www.xylem.com

USA
Xylem, Inc.
Cape Ann Industrial Park
Gloucester, MA 01930
Tel: (978) 281-0440
Fax: (978) 283-2619

UK
Xylem, Inc.
Bingley Road, Hoddesdon
Hertfordshire EN11 0BU
Tel: +44 (0) 1992 450145
Fax: +44 (0) 1992 467132

GERMANY
Xylem, Inc.
Oststrasse 28
22844 Norderstedt
Tel: +49-40-53 53 73-0
Fax: +49-40-53 53 73-11

JAPAN
NHK Jabsco Company Ltd.
3-21-10, Shin-Yokohama
Kohoku-Ku, Yokohama, 222-0033
Tel: +81-045-475-8906
Fax: +81-045-477-1162

ITALY
Xylem, Inc.
Via Tommaseo, 6
20059 Vimercate, Milano
Tel: +39 039 685 2323
Fax: +39 039 666 307